



DIVUS DIVA

DATASHEET

DIVA PC

DIVUS DIVA



FUNCTIONAL DATA SHEET

TECHNICAL DATA	DIVUS DIVA PC
Type of design	extra HIGH performance, ultra LOW power requirements MAXI Display with FULL HD resolution monocoque body shaped from a single block of aluminium ultra compact embedded Touch Panel for wall mount; noiseless and without any rotating part
FRONT UNIT	
Size / Type	22" - 55 cm LED Backlight TFT Display
Luminosity / Contrast	400 cd/m ² - 10.000 : 1
Resolution (in Pixel)	FULL HD 1920x1080
Response Time / Viewing angle	3 ms - 170° H - 160° V
MTBF backlight tubes	20.000 h
Method of operating	Resistive Window Touch with Multitouch function
Rating	IP20 according EN 60529
GENERAL CHARACTERISTICS	
Processor	Intel Celeron N2930 SoC, 1.83GHz - 2.16GHz burst, Quad-Core
Chipset	SoC
Memory	DDR3L-1333 up to 8GB total
Free expansion slots	-
Operating systems	Multilanguage Windows 10 IoT
Power Supply	90-260VAC auto range fanless included - to be mounted on DIN rail in MD/MD-A
Power consumption	max. 40 W
Guarantee	24 Months*
OPTIONAL ACCESSORIES - FUNCTIONAL	
LED Stripes	Multi-Colour LED Stripes with radio control
WLAN / Bluetooth	WLAN or Bluetooth module via USB
DRIVES	
Storage medium	high speed MSATA Flash Module - 60GB capacity
INTERFACES	
LAN/Ethernet	Realtek PCIe 10/100/1000 Mbit controller (ext)
USB (Universal Serial Bus)	2 x USB 3.0 (1 x ext)
Keyboard/Mouse	no PS/2
Multimedia	HDTV resolution up to 1080i capable 1 x free DVI-I port - DUAL Display architecture 2 x 3W sinus power speaker VOIP function - acoustic signals (ex: warnings, messages) - voice registration and playback in PC mode
WATCHDOG FUNCTIONS	
CPU Temperature	surveillance onboard, WDT integrated

*warranty ex works, normally 24 months, fixed at order. All data refer on print date, errors and changes excepted.
NOTE: Internal connections are intended as inside the box unit, normally on pin header, external ones as outside the box. Nevertheless, once mounted in the wall, only connections described as "front accessible" will be reachable for the customer.

DIVUS DIVA



MECHANICAL DATA SHEET

TECHNICAL DATA:		DIVUS DIVA PC	
Type of design	monocoque body shaped from a single block of aluminium ultra compact embedded PC for wall mount; noiseless and without any rotating part		
MECHANICAL CHARACTERISTICS			
Mounting direction	Landscape	Portrait	
	Vertically mounted in MD or MD-A mounting box		
	Optional, inclined by 37,5°	Optional, inclined by 12,5°	
	In wall mounting allowed		
Front	smooth surface touchscreen front, to use with the wall mount box (MDxx) and side-cover(SC-xx)		
PC Unit	alloy anodised monocoque enclosure, EMC proofed		
OPTIONAL ACCESSORIES – MOUNTING PARTS			
12,5° inclination kit	-	available	
37,5° inclination kit	available	-	
In wall mount box MD	necessary for in wall mounting		
On wall mount box MD-A	necessary for on wall mounting		
SIDE - COVERS			
SCg-B	Glass cover black		
SCg-W	Glass cover white		
SCg-V	Glass cover violet		
SC-A1	Aluminium cover anodized		
SC-A-RAL	Aluminium cover roughly, varnishing by DIVUS		
AMBIENT CONDITIONS			
Vibration/Shock resistance	15G / 50G		
EMC	EN 55011, 55022, 500081		
Temperature	+0°C to +30°C max.		
Relative humidity	5% to 80% at 25°C (no humidity/condense)		
Authorization	CE		
DIMENSIONS			
Cut-Out MD [mm]	632 x 447 x 144 plus plaster guide 15 mm		
Cut-Out MD-A [mm]	212 x 212 x 80		
Outside dimension [mm]	553 x 368 x 57 plus docking socket 200 x 200 x 20		
Weight	ca 12 kg		