

GERMAN
DESIGN
AWARD
SPECIAL
2017



DATASHEET: NOVEMBER 2018

DIVUS TOUCHZONE

The Synergy Touch

TZ07 - TZ10 - TZ15 - TZ19
VER.3

DIVUS TOUCHZONE



**TOUCH PANEL FOR WALL MOUNT
TECHNICAL DATA**



TZ07 - W



TZ10 - B



TZ15 - B



TZ19 - B

	TZ07 - V3	TZ10 - V3	TZ15 - V3	TZ19 - V3
--	-----------	-----------	-----------	-----------

Type of design	ultra compact embedded PC for wall mount; android operation system for your applications; noiseless and without any rotating part, ultra low power homogeneous smooth glass surface with aluminium side border			
----------------	--	--	--	--

VERSIONS

With Black cover glass	TZ07-B	TZ10-B	TZ15-B	TZ19-B
With White cover glass	TZ07-W (ultra clear glass)	TZ10-W (clear glass)	TZ15-W (clear glass)	TZ19-W (ultra clear glass)

SOFTWARE

Operating System	Android 6			
FRONT UNIT	7,0" - 17,78 CM WIDESCREEN LED BACKLIGHT TFT	10,1" - 25,6 CM WIDESCREEN LED BACKLIGHT TFT	15,6" - 39,6 CM WIDESCREEN TFT LED BACKLIGHT TFT	18,5" - 47,0 CM WIDESCREEN TFT LED BACKLIGHT TFT
Luminosity	500 cd/m ²	250 cd/m ²	300 cd/m ²	300 cd/m ²
Contrast	400 : 1	400 : 1	500 : 1	1000 : 1
Resolution (in Pixel)	WSVGA (1024*600)	WSVGA (1024*600)	HD (1366*768)	HD (1366*768)
MTBF backlight	50.000 h	30.000 h	50.000 h	50.000 h
Method of operating	Projected capacitive touch screen with 3 mm glass front, dual touch capable			
Rating	IP20 according EN 60529			

GENERAL CHARACTERISTICS

Processor	Fanless ultra low consumption Cortex-A53 Quad Core 1,5GHz			
Memory	2 GB (optional 4GB, connected to MOQ)			
Free expansion slots	microSD Slot			
Power Supply	PoE+ compatible with Cat5e/Cat6 UTP cable, max 100m IEEE Std 802.3at™			NO
	12-32 VDC			
Power consumption without peripherals	Max. 7 W	Max. 16 W	Max. 25 W	Max. 30 W
Guarantee	24 Months*			

DRIVES

Storage medium	High speed Flash Memory 16GB eMMC (available disk space tbd)			
----------------	--	--	--	--

DIVUS TOUCHZONE



TOUCH PANEL FOR WALL MOUNT TECHNICAL DATA

	TZ07-V3	TZ10-V3	TZ15-V3	TZ19-V3
SENSORS				
Proximity sensor	INCLUDED	INCLUDED	INCLUDED	INCLUDED
G Sensor for orientation	AUTOMATIC PORTRAIT / LANDSCAPE ORIENTATION			
Brightness Sensor	Q4 - 2018			
MULTIMEDIA				
Input/output	Loudspeaker 2 Watt RMS (ext) Microphone (ext)			
Functionality	Integrated Echo cancellation for bi-directional interphone communication			
INTERFACES				
LAN/Ethernet/BT	1 x GbE on RJ45 - 45 degree with 802.3at™ (ext) 1 x WiFi 802.11 a/b/g/n - optional 1 x Bluetooth 4.0 LE - optional			
USB (Universal Serial Bus)	2 x USB 2.0 (2x ext) 1 x mini USB OTG			
Serial	1 x RS-232/422/485 (int, optional on pinheader)			
Digital Input/Output	GPIO - 4 x Input / 4 x Output for 4 relais with max. 100 mA/5VDC Clocking is possible, frequency depends on APK			
Battery	Battery free system - RTC with capacitor backup			
SURVEILLANCE				
Status LEDs	1 x RGB LED - covered by design frame			
AMBIENT CONDITIONS				
EMC	EN 55011, 55022, 500081			
Temperature	+0°C to +30°C max.			
Relative humidity	5% to 80% at 25°C (no humidity/condense)			
Authorization	CE			
DIMENSIONS				
Cut-Out with MTZ [mm]	129 x 210 x 75	281 x 189 x 80	428 x 291 x 80	507 x 330 x 80
Outside with Frame CTZ [mm]	136 x 213 - This product is delivered with capacitive touch frame	288 x 200 - This product is delivered with capacitive touch frame	435 x 306 - This product is delivered with capacitive touch frame	515 x 345 This product is delivered with capacitive touch frame
Weight	0,9 kg	4 kg	7 kg	9 kg
MECHANICAL CHARACTERISTICS				
Mounting	Fast and easy one man mounting system with wall mount boxes			
Front	Steel and alloy anodized, to use with the wall mount box (MTZ) and cover (CTZ)			
PC Unit	EMC proofed	Alloy anodised, EMC proofed		

*warranty ex works, normally 24 months, fixed at order. All data refer on print date, errors and changes excepted.

NOTE: Internal connections are intended as inside the box unit, normally on pin header, external ones as outside the box. Nevertheless, once mounted in the wall, only connections described as "front accessible" will be reachable for the customer.

DIVUS TOUCHZONE



WALL MOUNT BOX

TYPES	IN WALL BOX	IN MORTARLESS BOX
for TZ07 – 7,0"	MTZ07	MTZ07-T
for TZ10 – 10,1"	MTZ10	MTZ10-T
for TZ15 – 15,6"	MTZ15	MTZ15-T
for TZ19 – 18,5"	MTZ19	MTZ19-T

TECHNICAL DATA

Type of design	compact, stable and flat wall mount box for flush mounting	compact flush mounting kit for mortarless constructions
----------------	--	---

DIMENSIONS [MM]

Cut-Out fixing kit 7,0"	129 x 210 x 75	129 x 210 x 75 - required space 190 x 210 x 75
Cut-Out fixing kit 10,1"	281 x 189 x 80	281 x 189 x 80 - required space 341 x 189 x 80
Cut-Out fixing kit 15,6"	428 x 291 x 80	428 x 291 x 80 - required space 488 x 291 x 80
Cut-Out fixing kit 18,5"	507 x 330 x 80	507 x 330 x 80 - required space 567 x 330 x 80
Weight	ca. 4kg	ca. 4kg


MECHANICAL CHARACTERISTICS

Wall mount box	TZ 7 plastic with cover for clean installation	TZ 7 plastic with cover for clean installation
	TZ 10 - 15 - 19 steel plate with cover for clean installation	TZ 10 - 15 - 19 steel plate with cover for clean installation
Cable access	1xtop, 1xbottom, 1xleft, 1xright	1xtop, 1xbottom, 1xleft, 1xright




Grounding the Wall Mount Box needs to be professionally grounded

MONTAGE / INSTALLATION INSTRUCTIONS / INSTALLAZIONE

 Die Unterputzdose und das Trockenbaukit können in einem Ausschnitt in der Wand oder in einem bis zu 1,5 cm dünnen Möbelstück, sowie in einem Trockenbau befestigt werden. Der Ausschnitt muss den in den technischen Details spezifizierten Maßen entsprechen und beim Wandeinbau mindestens 9 cm tief sein.

Im Wandausschnitt wird die Unterputzdose eingemauert, während sie im Möbelstück angeschraubt werden kann. Es ist wichtig, dass die vordere Kante der Unterputzdose plan und waagrecht zur Oberfläche der Wand oder des Möbelstückes ist.

 The wall mount box an the mounting kit may be installed in a cut out in the wall, in a wooden structure thick at least 1,5 cm or in a dry mortarless construction. The cut out has to respect the sizes specified in the technical data and has to be at least 9 cm deep. In the wall cut out, the box can become build in while it can be screwed on in a piece of furniture. It is important that the fore edge of the box is flat and horizontally to the surface of the wall or the piece of furniture.